



US005458096A

# United States Patent [19]

[11] Patent Number: **5,458,096**

Hollis

[45] Date of Patent: **Oct. 17, 1995**

[54] **HYDRAULICALLY OPERATED ELECTRONIC ENGINE TEMPERATURE CONTROL VALVE**

5,121,714 6/1992 Susa et al. .... 123/41.1  
5,195,467 3/1993 Kurz ..... 123/41.1

### FOREIGN PATENT DOCUMENTS

[76] Inventor: **Thomas J. Hollis**, 5 Roxbury Dr., Medford, N.J. 08055

53-136144 11/1978 Japan .  
5-35167 3/1980 Japan .  
1574860 6/1990 U.S.S.R. .... 123/41.08

[21] Appl. No.: **306,240**

### OTHER PUBLICATIONS

[22] Filed: **Sep. 14, 1994**

*Hydraulic Handbook*, Trade and Technical Press Ltd, 1-9, Tudor Dr., Morden, Surrey, 1957, p. 503.

[51] Int. Cl.<sup>6</sup> ..... **F01P 7/14**

Goodheart-Willcox automotive encyclopedia, The Goodheart-Willcox Company, Inc., South Holland, Ill., 1979, 101-125, 265-270.

[52] U.S. Cl. .... **123/41.1; 251/30.01; 251/61.4**  
[58] Field of Search ..... 123/41.08, 41.09, 123/41.1; 251/30.01, 61.4

Perry's Chemical Engineers' Handbook, Sixth Edition, McGraw Hill Book Co., New York, 1984, pp. 22-79 through 22-87.

### [56] References Cited

#### U.S. PATENT DOCUMENTS

2,277,113	3/1942	Kimmel	123/41.08
2,435,041	1/1948	Hild	123/196 AB
2,650,609	9/1953	Herbst	137/623
2,799,466	7/1957	Hickerson	251/30
4,079,715	3/1978	Masaki et al.	123/122 R
4,332,221	6/1982	Imhof et al.	123/41.08
4,348,991	9/1982	Stang et al.	123/41.29
4,357,912	11/1982	Brown	123/41.08
4,369,738	1/1983	Hirayama	123/41.1
4,399,775	8/1983	Tanaka et al.	123/41.08
4,399,776	8/1983	Shikata	123/41.08
4,423,705	1/1984	Morita et al.	123/41.02
4,484,541	11/1984	Yokoyama	123/41.1
4,539,942	9/1985	Kobayashi et al.	123/41.1
4,545,333	10/1985	Nagumo et al.	123/41.02
4,644,909	2/1987	Nishikata et al.	123/41.1
4,726,324	2/1988	Itakura	123/41.1
4,726,325	2/1988	Itakura	123/41.1
4,744,336	5/1988	Miller	123/41.1
4,754,693	7/1988	Teltscher	91/464
4,964,371	10/1990	Maeda et al.	123/41.1
4,982,902	1/1991	Knapp et al.	239/585
5,111,775	5/1992	Sumida et al.	123/41.1

Primary Examiner—Noah P. Kamen

Attorney, Agent, or Firm—Seidel Gonda Lavorgna & Monaco

### [57] ABSTRACT

A valve is employed to control the flow of temperature control fluid to a radiator in an internal combustion engine. The valve is hydraulically actuated by a pair of hydraulic fluid injectors to move between a first position for preventing the flow to a second position for allowing the flow. The valve reciprocates within a valve housing. The fluid injectors cause pressurized hydraulic fluid to be delivered to and removed from a chamber in the valve housing. The fluid pressure in the chamber pushes against a valve diaphragm or piston to cause the diaphragm or piston to move from a first state to a second state, thereby causing a valve member or valve piston shaft to move from the first position to the second position. The valve can also control the flow of temperature control fluid through the oil pan and around the intake manifold.

**49 Claims, 37 Drawing Sheets**

